



GENERAL CAR INFO		DIMENSIONS/CAPACITIES		SPECIALTY SUPPLIERS AND PART NUMBERS	
Built date	1975	Length (strikers)	61'-8"	Truck type	ASF Ride Control Floors
Car builder	Thrall	Coupled length	66'-0"	Bols. Patt. / AAR Code	22237-L/none
AFE number	75-156	Truck ctrs.	49'-2"	Side Frame/AAR Code	22052-BK/F9A-04BN-UA
AAR Mech. Des.	FB	Inside lg. Bet. Bulkheads	56'-8 1/2"	Truck spring group	8 D-5(O),8 D-5(I)
AAR Car Code	F242	Bulkhead width	10'-2 5/8"	Snubbing type	ASF Ride Control
GST Code	FB5	Bulkhead height	11'-0"	Snub. sprng. group	2 #3091(O), 2 #3092(I)
Clearance plate	C	Deck Width	10'-5"	Column wear plate	ASF 98-1-10043
C.G. - Empty	35"	Extreme height	14'-8 1/4"	Pedestal roof liners	Transdyne A-05013
C.G. - Loaded	86"	Extreme Width	10'-6"	Wheels	Griffin CH-36 1-W
Min. curve-Coupled	255R(22°)	Gross rail load	263,000 lbs.	Roller bearings	Timken E-24322-Q
Min. curve-Uncoupled	180R(32.3°)	Lightweight	75,122 lbs.	Adapter	Albion 6 1/2"x12"
Braking ratio - Empty	28.25%	Load limit @ 263K	187,878 lbs.	Truck side bearing	Stucki 688-B
Braking ratio - Loaded	7.95%	Floor Rating	50K	Horz. center plate liner	Manganese Steel
Braking ratio - H.B.	11.80%			Vertical wear ring	1/4", type 301 stainless
				Coupler/Knuckle	ASF E60CHT/E50HT
				Draft sill/Striker assy.	Fabricated
				Cp. carr. wear plt.	Manganese steel
				Uncoupling rod	Stanray CU-24820-A
				Draft Gear/Cushioning	F.M.I. E10, 87.14025
				Brake system	Body mounted
				Control valve	NYAB ABD
				Brake cylinder	NYAB 10" x 12"
				Slack adjuster	Universal U-1900-H
				Brake beam	Davis (#18)
				Brake beam wear elim.	Unit Truck Corp. UW-133
				Brake shoes	NYAB 2" Comp.
				Handbrake(250-349)	Equipco 4000-A
				Handbrake(350-449)	Universal 7400-B
				Load anchors	Ireco 30162
<b>FORMER ROAD NUMBERS</b>					
<b>NOTES AND EXCEPTIONS:</b>					
ved:11/14/95;SCL;Rev. B 05/08/97					