



GENERAL CAR INFO		DIMENSIONS/CAPACITIES		SPECIALTY SUPPLIERS AND PART NUMBERS			
Built date	1973	Length (strikers)	50'-5 1/2"	Truck type(300-679)	Dresser Barber S-2-C	Roller bearing(300-399)	Brenco HM 133444 6 1/2"x12"
Car builder	Greenville	Coupled length	53'-1"	Truck spring group	6 D-5 (O), 6 D-6 (I)	Roller bearing(400-690)	Timken HM 133444 6 1/2"x12"
AFE number	73-1262	Truck ctrs.	40'-6"	Snubbing type	Dresser Barber S-2-C	Roller bearing(691-770)	Hyatt 6 1/2"x12"
AAR Mech. Des.	HT	inside length	48'-1 1/2"	Snubber spring group	2 B-432 (O), 2 B-433 (I)	Roller bearing(771-779)	nken HM 133443XP 6 1/2"x12"
AAR Car Code	H351	inside width	9'-9 1/2"	Supp. Snubber	Stucki HS-6	Adapter	Albion 6 1/2"x12"
GST Code	H6R	Width (side posts)	10'-6 5/8"	Truck type(680-779)	ASF T-11	Truck side bearing (300-679)	Stucki 688-B
Type unloading	Gravity	Extreme width	10'-8"	Truck spring group	7 D-5 (O), 6 D-6 (I)	Truck side bearing (680-779)	ASF 75091-G
Clearance plate	B	Extreme height	12'-9"	Snubbing type	ASF T-11	Horz. center plate liner	Manganese Steel
C.G. - Empty	51.00'	Volume	4000 cu. ft.	Snubber spring group	2 #3251 (O), 2 #3252 (I)	Vertical wear ring	1/4" type 301 steel
C.G. - Level load	85.00'	Gross rail load	263,000 lbs.	Bolster patt./AAR cd(300-629)	Natl. 49212-6/none	Coupler/Knuckle - fixed	M&T F8508Ahte/F51HTE
C.G. - 10" Heap	89.33'	Lightweight	58,500 lbs.	Bolster patt./AAR cd(630-679)	Dresser BO-9361-HT/none	Coupler/Knuckle - rotary	Buckeye SF 13 HTE/F51HTE
Min. curve-Coupled	215'(27°)	Load limit @ 263K	204,500 lbs.	Bolster patt./AAR cd(680-779)	ASF 22236-A/none	Follower	M&T Y46 HTE
Min. curve-Uncoupled	150'(39°)			S.F. patt./AAR cd(300-399)	Dres. TF-9075-HT/F9S-OIDN-UA	Yoke(300-499)	M&T Y45Ahte
Braking ratio - Empty	27.67%			S.F. patt./AAR cd(400-629)	Natl. 46363-6/F9S-OIDN-UA	Yoke(500-779)	Buckeye Y45Ahte
Braking ratio - Loaded	6.15%			S.F. patt./AAR cd(630-679)	Dres. TF-9075-HT/F9S-OIDN-UA	Draft sill/Striker assy.	Buckeye D-11874
Braking ratio - H.B.	9.10%			S.F. patt./AAR cd(680-779)	ASF 22235-A/none	Cp. carr. wear plt.	Buckeye B-11341
				Column wear plate(300-399)	Dresser 4261	Uncoupling rod-fixed	Stanray CU-24107
				Column wear plate(400-629)	Natl. 49266	Uncoupling rod-fixed	Stanray CU-24106
				Column wear plate(630-679)	Dresser 4261	Uncoupling rod-rotary	Stanray CU-24108
				Pedestal roof liners	ASF 43141	Draft Gear/Cushioning	Miner RF-444
				Wheels(300-579)	Bethlehem H-36 1-W	Brake system	Body Mounted
				Wheels(580-779)	U.S. Steel H-36 1-W	Control valve	NYAB ABD
				Brake cylinder	NYAB 10"x12"	Slack adjuster	Elcon 2000-DJ
				Brake beam(300-579)	ASF (#18)	Brake beam(580-779)	Buffalo BB-252(#18)
				Brake beam wear elim.	Unit Truck Corp. UW-133	Brake shoes	Wabco 2" Comp.
				Handbrake(300-499)	Miner 6600	Handbrake(500-779)	Universal U-7400-G
				Hopper Door Arrgt.	Wine 4HF-1005-A		
<p><b>FORMER ROAD NUMBERS</b>  <b>BN 525300 - 525779</b></p>							
<p><b>NOTES AND EXCEPTIONS:</b></p>							
<p>Approved: 10/20/95; SCL; Rev. B 05/06/97</p>							
<p>PAGE G51</p>							